

IN THE CLAIMS

1. (Currently Amended) A method of modeling circulation in a living subject, such method comprising the steps of:
- simulating the fluid dynamics of an arterial circulatory system;
 - adapting the simulation to substantially conform to a specific arterial anatomy of the living subject;
 - forcing the simulation with a forcing function made up of one or more flow-time or pressure-time signatures;
 - calculating a flow of the circulatory system of the living subject based upon the forced simulation;
 - measuring a flow in the living subject corresponding to the calculated flow; and,
 - correcting the simulation ~~based upon the calculated and measured flows~~ by adjusting a flow resistance of the simulation based upon the ratio of the measured and calculated flows
2. (Previously Amended) The method of modeling as in claim 1 wherein the simulated circulatory system includes the Circle of Willis.
3. (Previously Amended) The method of modeling as in claim 1 further comprising the step of calculating a flow of the circulatory system based upon a selected blood flow perturbation.
4. (Previously Amended) The method of modeling as in claim 3 wherein the selected blood flow perturbation is a surgical alteration.
5. (Previously Amended) The method of modeling as in claim 1 wherein the step of adapting the simulation to substantially conform to the living subject's anatomy further comprises conforming a vessel of the simulation with a corresponding vessel in an image of the living subject.

6. (Previously Amended) The method of modeling as in claim 5 wherein the step of adapting the simulation to substantially conform to the living subject's anatomy further comprises measuring a diameter of the corresponding vessel in the image of the living subject.
7. (Previously Amended) The method of modeling as in claim 6 further comprising localizing the corresponding vessel in three-dimensional space and tracing a boundary into adjacent areas in three-dimensional space to locate respective ends of the corresponding vessel.
8. (Currently Amended) The method of modeling as in claim 1 wherein the step of correcting the simulation based upon the calculated and measured flows further comprises adjusting a flow resistance of the simulation based upon the ratio of the measured and calculated flows by multiplying a current value of the flow resistance by the ratio of the measured and calculated flows.
9. (Previously Amended) The method of modeling as in claim 8 wherein the simulation of the circulatory system includes a one-dimensional, explicit, finite difference algorithm based upon a conservation of mass equation, a Navier-Stokes momentum equation, and an equation of state relating local pressure to local artery size .
10. (Previously Amended) The method of modeling as in claim 1 wherein the simulation is forced with a flow measurement obtained from the living subject.
11. (Previously Amended) The method of modeling as in claim 1 wherein the simulation is forced with a pressure-time signature obtained from a prototypical measurement.
12. (Currently Amended) Apparatus for modeling circulation within a living subject, such apparatus comprising:
a computerized simulation of a model of an arterial circulatory system, wherein the model calculates simulation includes means for calculating blood flows in the circulatory system when the model is forced with a forcing function;

means for adapting the model of the circulatory system to substantially conform to a specific arterial anatomy of the living subject;

means for measuring a blood flow in the circulatory system of the living subject;

means for measuring a blood flow in the living subject corresponding to a flow calculated by the model; and,

means for correcting the model ~~based upon the calculated and measured flows~~ by adjusting a flow resistance based on a ratio of the measured and calculated blood flows.

13. (Previously Amended) The apparatus for modeling as in claim 12 wherein the circulation model further comprises the Circle of Willis.

14. (Previously Amended) The apparatus for modeling as in claim 12 further comprising means for calculating a flow of the circulatory system based upon a selected blood flow perturbation.

15. (Previously Amended) The apparatus for modeling as in claim 12 wherein the means for measuring blood flow is a phase contrast magnetic resonance angiography flow measurement system.

16. (Previously Amended) The apparatus for modeling as in claim 15 wherein the means for adapting the model to substantially conform to the living subject's anatomy further comprises means for selecting a vessel of the model and a corresponding vessel in an image of the living subject.

17. (Previously Amended) The apparatus for modeling as in claim 16 wherein the means for adapting the model to substantially conform to the living subject's anatomy further comprises means for measuring a diameter of the corresponding vessel.

18. (Previously Amended) The apparatus for modeling as in claim 17 further comprising means for localizing the corresponding vessel in three-dimensional space and tracing a boundary

into adjacent areas in three-dimensional space to locate respective ends of the corresponding vessel.

19. (Currently Amended) The apparatus for modeling as in claim 12 wherein the means for correcting the model adjusts a flow resistance ~~based on a ratio of the measured and calculated flows~~ by multiplying a current value of the flow resistance by the ratio of the measured and calculated blood flows.

20. (Previously Amended) The apparatus for modeling as in claim 12 wherein the computerized simulation model includes a one-dimensional, explicit, finite difference algorithm based upon a conservation of mass equation, a Navier-Stokes momentum equation, and an equation of state relating local pressure to local artery size.

21. (Previously Amended) The apparatus for modeling as in claim 12 wherein the model is forced with a flow measurement obtained from the living subject.

22. (Previously Amended) The apparatus for modeling as in claim 12 wherein the model is forced with a pressure-time signature obtained from a prototypical measurement.

23. (Currently Amended) A system for modeling circulation in a living subject, comprising:
a computerized fluid dynamics simulation of a model of an arterial circulatory system ~~which includes;~~

an adaptation module for adapting the ~~model~~ simulation to substantially conform to a specific arterial anatomy of the living subject;

a blood flow measurement device for obtaining a flow measurement from the living subject; and

~~wherein the model includes~~ a correction module for correcting the model based on a ratio of the measured flow and a corresponding flow calculated by the ~~model~~ simulation.

24. (Currently Amended) The system for modeling as in claim 23 wherein the ~~simulation~~ model includes the Circle of Willis.

25. (Previously Amended) The system for modeling as in claim 23 further comprising;
an imaging device for generating an image of the circulatory system of the living subject;
a display device for displaying the generated image of the circulatory system, the display device including a cursor adapted to select a vessel of the image, and,
wherein the selected vessel is input to the adaptation module in order to adapt the model to substantially conform to a specific arterial anatomy of the living subject.

26. (Previously Amended) The system for modeling as in claim 25 further comprising a pixel processing module for processing pixel data from the imaging device of the general area of the selected vessel to locate a boundary between the selected vessel and surrounding tissue.

27. (Previously Amended) The system for modeling as in claim 26 wherein the pixel processing module measures a diameter of the corresponding vessel.

28. (Previously Amended) The system for modeling as in claim 27 wherein the pixel processing module traces the boundary of the selected vessel into adjacent areas in three-dimensional space to locate respective ends of the corresponding vessel.

29-51 (Canceled)

52. (Previously Amended) The method of claim 1 further comprising the step of obtaining a flow measurement in the living subject by phase contrast magnetic resonance angiography.

53. (Previously added) The method of claim 1 further comprising the step of obtaining a flow measurement in the living subject by a Doppler flow measurement.

AMENDMENT AND RESPONSE UNDER 37 CFR § 1.116 – EXPEDITED PROCEDURE

Serial Number: 09/400365

Filing Date: September 20, 1999

Title: PATIENT SPECIFIC CIRCULATION MODEL

Page 8

Dkt: 1566.002US1

54. (Previously added) The apparatus for modeling as in claim 12 wherein the means for measuring blood flow is a Doppler flow measurement device.

55. (Previously Amended) The system of claim 23 wherein the flow measurement device is a phase contrast magnetic resonance angiography system.